



DOMESTIC HOT WATER TANKS WITH ONE DOUBLE HIGH
OUTPUT HEAT EXCHANGER

EV 2X15 S 200 60 HP

SAP код	305250
Capacity	183 L
Net weight	84 kg
Insulation	50 mm
Heat exchanger surface S1	2.56 m ²
Heat exchanger capacity S1	15.6 L
Heat losses ΔT 45K	59 W
Energy class	B
Maximum operational temperature	95 °C
Maximum operational temperature of the heat exchanger	110 °C



Rated pressure of the water tank	8 bar
Rated pressure of the heat exchanger	6 bar
Diameter	600 mm



Information

EV 2x15 S 200 60 HP

- **DOUBLE HIGH OUTPUT HEAT EXCHANGER** increases the efficiency of low-temperature heat sources.
- Decreased hydraulic resistance (pressure drop) of the heat exchanger with a larger diameter of the inlet and outlet on G1 1/2. (160 L model with inlets/outlets on G1).
- Heat exchangers with large surfaces for connection to heat pump or condensing gas boiler systems.
- Suitable to operation with low temperature heat sources.
- High quality **ENAMEL COATING** with **TESY CrystalTech PRO** technology.
- **MAGNESIUM ANODES PROTECTION** of the inner tank surface for extended product life.
- **HIGHLY EFFICIENT INSULATION** for minimal heat losses for models up to 500 L.

Serie information

EV 2x15 S 200 60 HP

The range includes models from 160 to 500 liters. DOUBLE HIGH OUTPUT HEAT EXCHANGER increases the efficiency of low-temperature heat sources.

*All pictures shown are for illustration purpose only. Actual product may vary due to product enhancement.

The weights indicated in this website are net values for reference purposes only. Actual product weights may vary due to production tolerances.